



## Supplier's Declaration of Conformity

### 47 CFR § 2.1077 Compliance Information

#### Type of equipment– Silent Tools™ Plus

<b>Model:</b>	Electronic unit	ST+:BT A 1PP	7210 110-01
		ST+:BT A 2PP	7210 110-02
		FCC id: PVH0946	
		IC id: 5325A-0946	

In combination with Turning Adapter of TB60D-\*, TB61D-\* (see appendix for naming)

#### Responsible Party – U.S. Contact Information

Sandvik Coromant  
1702 Nevins Road  
Fair Lawn, NJ 07410  
USA

Telephone number: 1-844-249-1134

Email: us.coromant@sandvik.com

#### FCC Compliance Statement

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

#### IC compliance

This Class A digital apparatus complies with Canadian ICES-003  
CAN ICES-3 (A)/NMB-3(A)

Test house: Intertek Semko AB, FCC:SE0002 / IC code:2042G

Sandviken/Sweden:

Date: 200420

Title / Signature:

Anders Watzinger / CEO

Lars Bergström, President SMS

USA/Canada

## Appendix:

The turning adapter is delivered in many design variants, see naming description.

Example:	TB61D-CY100C1770W4RB	
Product description		
	Product family	
TB	TB: Turning adaptor	
	Product type	
6	5: 4C dampened bars (sensor embedded) 6: 3C dampened bars (sensor embedded)	
	Product material group	
1	0: Steel 1: Carbide reinforced	
	Adaptor type	
D	D: Damped ( ): Not damped	
-		
	Machine side coupling	
CY	CY: Cylindrical	
	Bar diameter	
100	40, 50, 60 ...: Diameter size in millimeter A: Inch description, bar diameter given in 1/16 inch	
	Sensor type/signal connection	
C	A: Unsensored B: 1 sensor, connector type PP x1 C: 2 sensors, connector type PP x2 D: 1 or 2 sensors, connector type PPO	
	Functional length	
1770	400, 500, 865...: Length in mm (equal to body length for CY)	
	Work side coupling interface	
W	W... Wedge lock S... Serration Lock C... Coromant Capto® H... HSK	
	Work side coupling interface size	
4	1: 16 mm 2: 25 mm 3: 32 mm 4: 40 mm	6: 60 mm 8: 80 mm 0: 100 mm
	Work side coupling position	
R	R... Right L... Left N... Neutral 2... 2 couplings	
	Index	
B	( ): NA B: Europe/North America/Japan R: Repair X: Recondition	